



# Alvium G5

## Alvium G5-321

Alvium G5-321 innovative 5GBASE-T camera with Sony IMX900 CMOS global shutter sensor provides industrial performance for cost effective embedded and machine vision applications.

### General

Model	Alvium G5-321
Product series	Alvium G5
Status	Available

### Sensor

Sensor type	Area scan
Chroma	Mono or Color
Spectral range	300 nm to 1100 nm
Resolution	2,064 × 1,552 (3.20 MP)
Sensor model	Sony IMX900
Sensor architecture (material)	cmos
Shutter type(s)	Global Shutter
Sensor size	4.6 × 3.5 mm (5.8 mm, Type 1/3.1)
Pixel size	2.25 μm × 2.25 μm

### Pixel formats

Sensor bit depth	10-bit, 12-bit, 8-bit
YUV pixel formats	YCbCr411_8_CbYYCrYY, YCbCr422_8_CbYCrY, YCbCr8_CbYCr
RGB pixel formats	BGR8, RGB8 (default)
Bayer pixel formats	BayerRG12

### Timing and gain

Max. frame rate	111 fps
Exposure time	7 μs to 10 s

## Timing and gain

Gain	0.0 dB to 48.0 dB
------	-------------------

## I/Os and power

Non-isolated lines	2 GPIOs (LVTTTL)
--------------------	------------------

Opto-isolated lines	1 input, 1 output
---------------------	-------------------

Power supply	10.8 to 26.4 VDC AUX   IEEE 802.3af, Power Class 0 PoE
--------------	--

Power consumption	External power: 4.9 W at 12 VDC (typical)   Power over Ethernet: 5.4 W (typical)
-------------------	--

## Operating conditions

Operating temperature (housing)	-20 °C to 60 °C ((housing))
---------------------------------	-----------------------------

## Mechanical properties

Body dimensions (L x W x H in mm)	60 × 29 × 29
-----------------------------------	--------------

Lens mount(s)	C-Mount, CS-Mount, S-Mount
---------------	----------------------------

Weight	100 g
--------	-------

## On-board memory and FPGA

Image buffer (RAM)	512 MByte
--------------------	-----------

Non-volatile memory (Flash)	1024 KByte
-----------------------------	------------

## Interfaces

Digital interface	IEEE 802.3: 5GBASE-T or 2.5GBASE-T (NBASE-T) and 1000BASE-T, IEEE 802.3af Power Class 0 PoE
-------------------	---

Technical Drawing

