# U3-34F4XLS-C-HQ Rev.1.2 (1010686)

**In series**
The model is in series and available for the long term.



## Specification

### Sensor

| | |
|---|---|
| Sensor type | CMOS Color |
| Shutter | Rolling shutter |
| Sensor characteristic | Linear |
| Pixel Class | 5 MP |
| Resolution | 5.11 Mpix |
| Resolution (h x v) | 2608 x 1960 Pixel |
| Aspect ratio | 4:3 |
| ADC | 12 bit |
| Color depth (camera) | 12 bit |
| Optical sensor class | 1/2.8" |
| Optical Size | 5.216 mm x 3.920 mm |
| Optical sensor diagonal | 6.52 mm 1/2.8" |
| Pixel size | 2 µm |
| CRA (Chief Ray Angle) | 0 ° |
| Manufacturer | Sony |
| Sensor Model | IMX675-AAQR1-C |
| Gain (master/RGB) | 26.8x/- |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 1056 / 48 |
| AOI image height / step width | 956 / 4 |
| AOI position grid (horizontal/vertical) | 2 / 4 |
| Binning horizontal | increased frame rate |
| Binning vertical | increased frame rate |
| Binning method | Horizontal: mean / Vertical: mean |
| Binning factor | 2x2 |
| Decimation (subsampling) horizontal | - |
| Decimation (subsampling) vertical | - |
| Decimation (subsampling) method | - |
| Decimation (subsampling) factor | - |







IDS Imaging Development Systems Inc.
92 Montvale Ave, Suite 4750 · Stoneham, MA 02180, USA · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com

## Model

| | |
|---|---|
| Frame rate freerun mode | 41 fps @ 10Bit |
| Frame rate trigger (continuous) | 41 fps @ 10Bit |
| Frame rate trigger (maximum) | 41 fps @ 10Bit |
| Exposure time (minimum - maximum) | 0.012 ms - 1999 ms |
| Long exposure (maximum) | 120036 ms |
| Power consumption | 0.5 W - 1 W |
| Image memory | - |

## HDR

| | |
|---|---|
| Mode | ClearHDR |

## Ambient conditions

For PCB versions, refer to the separate hints in the respective documentation.

| | |
|---|---|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F |
| Allowed device temperature during storage | -20 °C - 80 °C / -4 °F - 176 °F |
| Humidity (relative, non-condensing) | 20 % - 80 % |

## Connectors

| | |
|---|---|
| Interface connector | USB 3.0 micro-B |
| I/O connector | 8-pin Wuerth connector |
| Power supply | USB cable |

## Pin assignment I/O connector

| | |
|---|---|
| 1 | Voltage output 3.3 V |
| 2 | Ground (GND) |
| 3 | Flash output without optocoupler - Line 1 |
| 4 | Trigger input without optocoupler - Line 0 |
| 5 | General Purpose I/O (GPIO) 1 - Line 2 |
| 6 | General Purpose I/O (GPIO) 2 - Line 3 |
| 7 | Ground (GND) |
| 8 | USB Power: 5 V, max. 400 mA |




## Design

| | |
|---|---|
| Lens Mount | CS- / C-Mount |
| IP code | - |
| Dimensions H/W/L | 32.5 mm x 32.5 mm x 14.0 mm |
| Mass | 17 g |
| Housing material | - |

## Features

List of on-camera image pre-processing features.
All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).


IDS Imaging Development Systems Inc.
92 Montvale Ave, Suite 4750 · Stoneham, MA 02180, USA · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com

## U3-34F4XLS-C-HQ Rev.1.2 (1010686)

| | | |
|---|---|---|
| Image Acquisition | Freerun | ✓ |
| | Software trigger | ✓ |
| | Hardware trigger | ✓ |
| | Trigger controlled exposure | - |
| | Denoiser | - |
| | Long exposure | ✓ |
| | Line scan | - |
| | Global start | - |
| Flashing | Flashing | - |
| | PWM flashing | - |
| Image Adjustments | Auto exposure | - |
| | Auto gain | - |
| | Auto whitebalance | - |
| | Color correction | - |
| | Gamma | - |
| | LUT | - |
| | Mirror/flip | X/Y |
| On-board Image Processing | Pixel formats | BayerRG10g40IDS<br>BayerRG12g24IDS |
| | Region of interest | ✓ |
| | Decimation (FPGA) | - |
| | Decimation (Sensor) | |
| | Binning (FPGA) | - |
| | Binning (Sensor) | 2x2<br>Increases frame rate. |
| Others | Chunks | - |
| | Sequencer | - |
| | Events | - |
| | Firmware update | ✓ |
| | 1st supported firmware version | 3.34 |



IDS Imaging Development Systems Inc.
92 Montvale Ave, Suite 4750 · Stoneham, MA 02180, USA · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com