

■ 2472 x 2064

■ 103 fps

Go-X Series 

**GIG**  
VISION

❖ **GOX-5105-5GE**  
5.1-megapixel CMOS global shutter



- **High performance camera with 5.1-megapixel resolution**
- **1/1.8" CMOS imager (global shutter) features backside illuminated pixel technology**
- **2472 x 2064 resolution with 2.74  $\mu\text{m}$  square pixels**
- **Up to 103 fps over high performance 5GBASE-T interface (5 gigabits per second)**
- **Can auto-negotiate to 2.5GBASE-T and standard GigE (1000BASE-T)**
- **8/10/12-bit output in choice of monochrome or raw Bayer color models**
- **Flexible ROI & rescaling function (Xscale) for sub-pixel color/mono binning and resolution matching**
- **Traditional 1x2, 2x1, or 2x2 binning also included on monochrome models**
- **Horizontal/vertical image flip function, plus blemish compensation and shading correction**
- **Bayer model includes 5x5 debayering function plus built-in color conversion and temperature presets**
- **Includes Sequencer function and Automatic Level Control (ALC) for dynamic lighting conditions**
- **Compact size with excellent shock and vibration resistance**
- **Accepts power over GigE Vision interface or via separate 6-pin connector**
- **C-mount lens mount**

**JAI**<sup>®</sup>

# Specifications for GOX-5105-5GE


# Go-X Series

Specifications		GOX-5105-5GE
Sensor	1/1.8" CMOS global shutter (IMX547)	
Active pixels	2472 (h) x 2064 (v)	
Frame rate, full frame	103 frames/sec. @ 8-bit mono/Bayer	
Active area	6.8 mm (h) x 5.6 mm (v) - 8.82 mm diagonal	
Pixel size	2.74 $\mu\text{m}$ x 2.74 $\mu\text{m}$	
Read-out modes	Full ROI (single) 2472 (h) x 2064 (v) up to 103 fps H: 96 to 2472 pixels in 8 pixel steps V: 8 to 2064 lines in 2 line steps ROI (multi) Binning Up to 64 scanning areas - no overlap 1x2, 2x1, 2x2 (mono only)	
Image scaling (Xscale)	Supports independent, sub-pixel rescaling of H and/or V resolution (1/16 max.)	
EMVA 1288 Parameters	12-bit output format	
Absolute sensitivity	Mono: 4.37 p Color: 1.86 p ( $\lambda = 527 \text{ nm}$ )	
Maximum SNR	Mono: 38.71 dB Color: 38.78 dB	
Traditional SNR (Dark)*	>60 dB mono, >60 dB color (0 dB gain, 10-bit)	
Video signal output	Monochrome: 8/10/12-bits Color: 8/10/12-bit Bayer or 24/32-bit RGB	
Gain	Manual/auto 0 dB to +42 dB	
White balance	Off, presets, or one-push/continuous AWB	
Gamma/LUT	0.45 to 1.0 (9 steps) or 257-point programmable LUT	
Time synchronization	Support for Precision Time Protocol (IEEE 1588)	
Trigger input	Opto In, Pulse Generators (4), Software, NAND Out (2), User Output (4), Actions	
Exposure modes	Timed/EPS, RCT, Trigger Width, Auto	
Electronic shutter	Timed: 3.45 $\mu\text{s}$ to 8 sec. in 1 $\mu\text{s}$ steps Auto: 100 $\mu\text{s}$ to 9.7 ms at full resolution	
Auto Level Control (ALC)	Shutter range from 100 $\mu\text{s}$ to 9.7 ms, gain range from 0 dB to +42 dB. Tracking speeds and min/max values adjustable.	
Shading correction	Flat shading, color shading (color model)	
Video processing functions	H & V flip (mirroring), blemish compensation, edge enhancement, color conversion (color model)	
Operating temp. (ambient)	-5°C to +45°C (20 to 80% non-condensing)	
Storage temp. (ambient)	-25°C to +60°C (20 to 80% non condensing)	
Vibration	10G (20 Hz to 200 Hz, XYZ directions)	
Shock	80G	
Regulations	CE(EN 55032:2015(CISPR32:2015), EN 55035:2017(CISPR35:2016)), FCC Part 15 Class A, RoHS/WEEE, KC	
Power	6-pin PoE	+10V to +25V DC. 5.1 W typical @ +12 V +36V to +57 V DC. 6.7 W typical @ +48 V
Lens mount	C-mount	
Dimensions (H x W x L)	29 mm x 29 mm x 68 mm	
Weight	95 g	

## Ordering Information

GOX-5105M-5GE	Monochrome camera with 5GigE Vision interface
GOX-5105C-5GE	Color camera with 5GigE Vision interface

## Dimensions



## Connector pin-out

### DC In / Trigger

HIROSE HR10A-7R-6PB(73)


Pin	Signal
1	DC in +10V to +25V
2	Opto In+
3	Opto In-
4	Opto Out+
5	Opto Out-
6	Ground

### 5GigE Vision Interface

RJ45 with locking screws

Pin	Signal
1	TRD+ (0)
2	TRD- (0)
3	TRD+ (1)
4	TRD+ (2)
5	TRD- (2)
6	TRD- (1)
7	TRD+ (3)
8	TRD- (3)

## Spectral Response



\*Traditional SNR is based on random noise in a single frame, where EMVA SNR measurements consider more comprehensive noise sources and variance over time.

**Europe, Middle East & Africa**  
 Phone +45 4457 8888  
 Fax +45 4491 8880

**Asia Pacific**  
 Phone +81 45 440 0154  
 Fax +81 45 440 0166

**Americas**  
 Phone (Toll-Free) 1 800 445 5444  
 Phone +1 408 383 0300



Visit our website on [www.jai.com](http://www.jai.com)

See the possibilities

Company and product names mentioned in this datasheet are trademarks or registered trademarks of their respective owners. IAI-A-S cannot be held responsible for any technical or typographical errors and reserves the right to make changes to products and documentation without prior notice.