

Z-TRAK2 V-2K SERIES

Factory Calibrated High-Performance 3D Profile Sensors



FEATURES

- Scan speed 10K profiles/sec, 2,000 points/profile
- Factory calibrated real-time measurements in real-world units
- Unified Measurement Space for 360° in-line inspection and measurements
- Handles highly reflected surfaces
- Built-in reflection compensation algorithms
- Multi-Sensor synchronization
- Simplified cabling
- Compact IP67 housing for harsh operating environments
- Free bundled software:
 - Sherlock™ for rapid application deployment
 - Sopera™ LT SDK for scan and control
 - Sopera™ Pro run-times
 - 3rd party software support for 3D image processing

The New Z-Trak2 Family of 3D Profile Sensors Delivers 10,000 Profiles/Sec for In-Line Measurement and Inspection Applications.

The Z-Trak2 V-2K Series combines speed and performance with easy to use software to deliver highly accurate, real-time results for a wide variety of 3D measurement and inspection applications in electronics, PCB, wafer, flat-panel, factory automation, food processing, and secondary battery markets.


The Z-Trak2 V-2K Series delivers 2K points per profile with a larger FOV and scan speeds beyond 10K profiles/sec. Combined with its hardware-based reflection compensation algorithms and single-scan HDR capabilities, the Z-Trak2 V-2K Series supports a variety of FOVs with blue and red laser configurations.

HIGH DYNAMIC RANGE (HDR) IMAGING

Powered by Teledyne's 3D image sensor technology, the Z-Trak2 family features built-in single-scan HDR capability. This allows Z-Trak2 to scan objects made of highly reflective surfaces like machine aluminum/glass and low reflectivity materials like rubber, plastic, etc. at the same time. The HDR capability helps reduce processing complexity and time, thereby improving system efficiency.

REFLECTION ELIMINATION AND IN-LINE PROCESSING

Z-Trak LP2C features in-line processing capabilities to improve and enhance the profiles. In addition, it can generate additional meta data that can be used by up-stream algorithms to eliminate un-wanted reflections. Cleaner 3D scans help applications produce accurate and dependable results.




MULTI-SENSOR CONFIGURATION AND UNIFIED MEASUREMENT SPACE (UMS)

3D inspection applications requiring 360° views, thickness measurement, an extended horizontal field of view without sacrificing the z-resolution or removing occlusion etc. require the combination of multiple profile sensors.

Combining and synchronizing multiple Z-Trak LP sensors helps create a Unified Measurement Space so that applications view the resulting 3D measurements from the point of view of the entire system. The 3D applications benefit from consistent, accurate and easier to handle object measurements and for added flexibility, the Z-Trak LP architecture also enables models with different measurement ranges and laser colors to be combined.



Z-TRAK UNIFIED MEASUREMENT SPACE





Z-EXPERT 360° View Using 4 Synchronized Z-Trak Sensors

SPECIFICATIONS¹

Function	Description
Scanning Rate	<ul style="list-style-type: none"> • AOI: Up to 10K profiles/sec
Connectors	<ul style="list-style-type: none"> • 1 x M12 17-pin: Controls • 1 x M12 8-pin X-Coded: Data Ethernet port
Image Enhancements	<ul style="list-style-type: none"> • Single scan HDR • Reflection elimination • Specular configuration • Filters: programmable median • Horizontal and vertical flip • Unified Measurement Space
Multi-Sensor Sync	<ul style="list-style-type: none"> • Single low-cost wiring using off-the-shelf network switches • Sensor grouping • Configuration wizard to ease timing setup
Lasers	<ul style="list-style-type: none"> • Red: 660 nm 2M or 3R • Blue: 405 nm 2M or 3R
Reflectance Management	<ul style="list-style-type: none"> • Time integration • Laser power control: Automatic or manual • Gain control
Output Format	<ul style="list-style-type: none"> • Individual profile, range map and 3D point cloud • Depth (Z), Lateral (X), Reflectance (R) or Laser Peak Width (W) • GenICam 3.0 (SFNC 2.3) compatible 3D Data output formats compatible with • Calibrated Z; Rectified Z; Calibrated ZR/ZR+W • Native values and world units (microns/mm/inch) • 16-bit mono (1D line-scan mode) • 10-bit mono (2D area-scan mode)
Temperature	Storage: <ul style="list-style-type: none"> • -40° C to +80° C (-4° F to +176° F) temperature • 20% to 80% non-condensing relative humidity Operating: <ul style="list-style-type: none"> • 10° C (50° F) to 50° C (122° F) • Relative Humidity: up to 90% (non-condensing)
System Requirements	<ul style="list-style-type: none"> • 1 Gigabit Ethernet • 4 GB or higher system memory
I/O	<ul style="list-style-type: none"> • 2 opto-isolated input • Configurable as a trigger input or as a start/stop trigger • 2 opto-isolated output • Serial communication port² or Analog output² 4 – 20 mA
Encoder Input	<ul style="list-style-type: none"> • Quadrature (AB) shaft-encoder inputs • RS422/TTL • Up to 5 MHz (20M tick rate) • Backlash compensation



Function	Description
Scan Control	Profile Trigger <ul style="list-style-type: none"> • Encoder input, Internal timer/counter Fixed Scan <ul style="list-style-type: none"> • External input; Software; Timer/counter Variable Scan <ul style="list-style-type: none"> • Part in place; Start/Stop pulse
Unified Measurement Space	<ul style="list-style-type: none"> • Intuitive GUI for rapid setup • Up to 16 sensors • Supports multiple sensors in side-by-side, circular and in-line configurations • Combine red and blue laser models • Supports models with different measurement ranges
Power Supply	<ul style="list-style-type: none"> • PoE via 8-pin X-code circular connector (optional) • Separate power via 12M 17-pin connector • +12V to 36VDC +/-10% with surge protection
Enclosure	<ul style="list-style-type: none"> • Machined aluminum • IP67 • 4 x mounting holes
Software	<ul style="list-style-type: none"> • Microsoft® Windows® 10 (32/64-bit) compatible • Linux 32/64-bit: <ul style="list-style-type: none"> • Ubuntu/Debian, RHEL/CentOS/Fedora, SLES/openSUSE • Kernel: 2.6.32 or higher • Fully supported by Teledyne DALSA's software packages (bundled free): • Free Software <ul style="list-style-type: none"> • Sherlock 8.0 • Sapera LT 8.60 (or higher), Sapera Processing 8.0 (or higher) RTL • Linux: Teledyne DALSA GevAPI Framework (SDK) ver. 2.40 or higher • 3rd party software: <ul style="list-style-type: none"> • MVTec® Halcon® • NI® Max/Labview® • Cognex® VisionPro® • Stemmer CVB • Application development using C++ and Microsoft .Net (C++, C# or Visual Basic)
Markings	<ul style="list-style-type: none"> • FCC Class B, CE, ICE • ROHS, China RoHS




SPECIFICATIONS¹ (Continued)

Models	V2K-0004-B3	V2K-0015-B3	V2K-0030-B3	V2K-0100-B3
Z-Range (mm)	4	15	30	100
Standoff Distance (mm)	33.15	32.7	43.7	64.5
Data Interface	1 GigE			
Z-Resolution (µm)	1 - 1	1 - 2	3 - 5	8 - 14
NFOV-FFOV (mm)	14.3 - 15.3	27 - 32	53 - 72	97 - 185
X-Resolution (µm)	7.03 - 7.80	14 - 17	27 - 37	50 - 95
Repeatability (+/-µm) ²	0.15 - 0.15	0.25 - 0.25	0.3 - 0.4	0.5 - 0.75
Linearity (% of F.S.)	<0.05%	<0.04%	<0.03%	<0.02%
Laser (nm) ³	405	405	405	405
Laser Class	2M / 3R	2M / 3R	2M / 3R	2M / 3R
Housing Type	T10	T20	T20	T20

Models	V2K-0150-R3	V2K-0250-R3	V2K-0300-R3	V2K-0400-R3	V2K-0650-R3
Z-Range (mm)	150	250	300	400	650
Standoff Distance (mm)	135	175	195	463	558
Data Interface	1 GigE				
Z-Resolution (µm)	14 - 25	22 - 45	34 - 74	43 - 71	81 - 156
NFOV-FFOV (mm)	129 - 228	157 - 325	230 - 508	400 - 659	624 - 1211
X-Resolution (µm)	66 - 117	81 - 167	118 - 261	206 - 339	321 - 623
Repeatability (+/-µm) ²	1 - 1.5	1.5 - 2	2 - 4	3 - 10	4 - 12.5
Linearity (% of F.S.)	<0.02%	<0.02%	<0.02%	<0.02%	<0.02%
Laser (nm) ³	660	660	660	660	660
Laser Class	2M / 3R	2M / 3R	2M / 3R	2M / 3R	2M / 3R
Housing Type	T30	T30	T30	T40	T40



1. Subject to change without prior notice
2. $\pm 2\sigma$
3. Contact Teledyne DALSA for other laser options

Housing Type	Size (L x H x W) (mm)
T10	165 x 97 x 49
T20	116 x 83 x 49
T30	177 x 83 x 49
T40	380 x 83 x 49

FOR MORE INFORMATION CONTACT:

AMERICAS Boston, USA | +1 978-670-2000 | TDI_sales.americas@teledynedalsa.com
EUROPE Krailling, Germany | +49 89-89-54-57-3-80 | TDI_sales.europe@teledynedalsa.com
ASIA PACIFIC Tokyo, Japan | +81 3-5960-6353 | TDI_sales.asia@teledynedalsa.com
 Shanghai, China | +86 21-3368-0027 | TDI_sales.asia@teledynedalsa.com

This document does not contain information whose export/transfer/disclosure is restricted by the Canadian Export Control regulation. Teledyne DALSA has its corporate offices in Waterloo, Canada. Teledyne DALSA reserves the right to make changes at any time without notice. © Teledyne DALSA.

Revision Number: N/A
 Revision Date: 2024 10 17