

Genie C1400-2/3

Area Scan Color Cameras



Overview

Small compact GigE Vision camera with uncompromised image quality.

The C1400 uses a Sony CCD, color bayer sensor resolution of 1360 x 1024. Operating at 15 frames per second at full resolution, the Genie C1400 takes advantage of gigabit Ethernet technology, transmitting data over standard CAT-5e and CAT-6 cables to distances of up to 100 m. Like all Genie cameras, the C1400 is based on AIA (Automated Imaging Association) GigE Vision Standard to directly link the camera to a PC.



Key Features

- Uses standard PC and server Ethernet ports & hardware
- Supports cable lengths up to 100 m (CAT-5e or CAT-6)
- Simplified set-up with field proven Sopera Essential software featuring CamExpert
- Engineered to accommodate industrial environment with a Ruggedize, screw mount, RJ-45 connector
- Small compact form factor

Programmability

- Achieve 15 fps in full resolution
- Higher frame rates achievable in partial scan mode
- Global electronic shutter with exposure control
- Programmable LUT
- On-board flat-field correction
- On-board Color conversion

Typical Applications

- Electronics manufacturing inspection
- Food inspection
- Intelligent traffic systems

Specifications


Active Resolution	1360 x 1024
Frame Rate	15 fps
Pixel Size	6.45 μm
Data Format	32-bits, YUV or Raw Bayer
Exposure Control	Programmable, or via External Trigger
Dynamic Range	57 dB
Nominal Gain Range	-6 dB to +12 dB
Output	Gigabit Ethernet, also supports 100 Mbps
I/O Ports	2 opto-isolated input, 2 opto-isolated output,
Lens Mount	C or CS-mount
Size	44 mm x 29 mm x 67 mm (including lens adapter)
Mass	~115 g (without lens)
Operating Temp	0°-45°C
Power Supply	12 V
Power Dissipation	4W
Data Connector	Standard or Screw mount RJ-45
Power and I/O	Hirose 12-Pin
Software Platform	DALSA Sopera LT
GigE Vision Compliant	Yes
Regulatory Compliance	FCC Class A, CE RoHS 2002/95/EC
Part Number	CR-GEN3-C1400



Genie C1400-2/3

Area Scan Color Cameras

All Genie cameras feature value added functionality designed specifically for imaging and machine vision applications. All features are easily accessible with DALSA's advanced software tools. These tools deliver superior image capture, performance, and control.



C or CS-mount: 1" diameter
32 threads per inch

