

Product Overview

XGS 20000: CMOS Image Sensor, 20.2 Mp, Global Shutter

For complete documentation, see the data sheet.

Advance Information

The XGS 20000 is a 20.3 Mp (4500 x 4500) CMOS image sensor in 1.3 inch optical format with 1:1 (square) aspect ratio, supporting up to 58 frame per second readout with 12-bit output at full resolution.

The device provides high resolution, global shutter imaging with high readout speed and a low power footprint for industrial imaging customers. Two speed grades are available to match device output to key computer interfaces and application requirements.

The XGS 20000 shares a common design and footprint with other members of the XGS family, such as the XGS 30000 or XGS 45000, allowing one camera design to support multiple resolutions to simplify and speed time to market for new camera designs.

The XGS 20000 is available in a 251-pin µPGA package in both monochrome and Bayer color configurations.

Features

- · Advanced 3.2 µm global shutter pixel
- · Energy efficient design
- · Available speed grades
- 1:1 (square) aspect ratio

Applications

· Image capture

Benefits

- · High resolution with high image quality and uniformity
- · Reduced power and thermal footprints
- Match to key computer interfaces and application requirements
- · Maximize image capture within lens optical circle

End Products

- · Industrial cameras and systems
- Inspection system (food, bottles, recycling labels, etc.)
- · Security cameras and systems
- · Machine Vision camera
- Broadcasting

Part Electrical Specifications												
Product	Pricing (\$/Unit)	Compliance	Status	Туре	Megapix els	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
NOIX0SE020KB-GTI-E		Pb-free Halide free non AEC-Q and PPAP	Active	CMOS	20.3	58	1.3 inch	Global Shutter	3.2 x 3.2	HiSPi™	Bayer Color	CPGA25 1 44.40x37 .25
NOIX0SN020KB-GTI-E		Pb-free Halide free non AEC-Q and PPAP	Active	CMOS	20.3	58	1.3 inch	Global Shutter	3.2 x 3.2	HiSPi™	Mono	CPGA25 1 44.40x37 .25

For more information please contact your local sales support at www.onsemi.com.

Created on: 9/16/2020