


Home | Accessories | LTRN series | LTRN 245 W45

## LTRN 245 W45

Ring LED illuminator, white

Light color, peak wavelength		white, 6300 K	
Optimal working distance	(mm)	20-80	
Illuminance at minimum working distance	(lux)	5900	
Illuminance at maximum working distance	(lux)	8800	
Lighting area diameter			
Outer	(mm)	245	
Inner	(mm)	158.5	
Electrical specifications			
Number of LED rows		1	
Continuous mode 1			
Supply voltage	(V)	24	
Current	(mA)	1200	
Power consumption	W	28.8	
Pulsed mode 2			
Supply voltage 3	(V)	24-48	
Pulse current	(mA)	3600	
Max. trigger pulse duration	(ms)	10	
Duty cycle	(%)	0-10	
Mechanical specifications			
Outer diameter	(mm)	245	
Inner diameter	(mm)	117	
Height	(mm)	38	
Mass	(g)	1130	
Cooling method	Attached to mach	Attached to machine part for better heat dissipation	
Compatibility			









## NOTES

- 1. Lifespan: 20.000 hours (drop to 50% intensity) at 25 °C.
- 2. Pulse width <= 10 ms, 0-10% duty cycle.
- 3. Recommended at 36 V.

Compatible products

PCPW0xx