

TC 16M 080


Bi-telecentric lens for 35 mm detectors, magnification 0.463 x, F-mount

Magnification	(x)	0.463
Image circle	(mm)	43.3

Object field of view		
with 2k x 10 µm detector	(mm)	44.2
with 4k x 7 µm detector	(mm)	61.9
with 8k x 5 µm detector	(mm)	88.4
with 36 x 24 mm detector	(mm x mm)	77.7 x 51.8

Optical specifications		
Working distance (1)	(mm)	198.0
f/# (2)		16
Telecentricity typical (max) (3)	(deg)	< 0.03 (0.08)
Distortion typical (max) (4)	(%)	< 0.09 (0.20)
Field depth (5)	(mm)	5
CTF@ 70 lp/mm	(%)	> 30

Mechanical specifications		
Mount		F
Length (6)	(mm)	406.4
Diameter	(mm)	116
Mass	(g)	1840



NOTES

- Working distance: distance between the front lens and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number: the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a very sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 4.8 µm.
- Measured from the front end of the mechanics to the camera flange.

COMPATIBLE PRODUCTS



LTCLHP080-G
Telecentric HP illuminator, beam diameter 100 mm, green



CMHO 080
Clamping mechanics for TCxx072, TCxx080, LTCL080-X illuminators and PCxx030XS



LTRN 080 NW
Ring LED illuminator, white